

### **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### **Listing of Claims:**

(Currently Amended) 1. A container, comprising:

a base;

a body portion attached to the base;

a concave waist attached to the body portion and having a surface, the surface including a plurality of axial apexes and troughs alternately arranged around the waist and configured to improve hoop strength of the waist and to maintain top load strength;

a first ridge and a second ridge arranged on either side of the waist, the apexes and the troughs of the surface being recessed with respect to both of the first and second ridges, the surface being 20%-40% thicker than the ridges;

a dome attached to the waist; and

a finish attached to the dome, the finish having an opening.

(Original) 2. The container of claim 1, further comprising a first surface portion extending inwardly and downwardly from the dome to the waist;  
a second surface portion extending inwardly and upwardly from the body to the waist.

(Canceled) Claim 3.

(Original) 4. The container of claim 1, wherein the waist unitarily connects the body and dome.

(Previously Amended) 5. The container of claim 3, the first ridge has a diameter that is less than equal to or greater than a diameter of the second ridge.

(Original) 6. The container of claim 1, further comprising panels connecting the apexes and trough, the panels arranged end to end.

(Original) 7. The container of claim 6, wherein each panel has one end connected at an apex and one end connected at a trough.

(Previously Amended) 8. A container, comprising:

a finish;

a dome attached to the finish, the dome extend from the finish to a first ridge having a first diameter;

a body having a second ridge with a second diameter;

a reduced diameter portion connecting the first ridge and the second ridge, the reduced diameter portion having a surface comprised of a plurality of panels, the panels being 20%-40% thicker than the first and second ridges and having side edges adjacent to side edges of an adjacent panel and being alternately inclined and declined with respect to each other around the reduced diameter portion.

(Canceled) Claim 9.

(Currently Amended) 10. The container of claim 89, wherein one side edge of a side panel forms an apex and the other side edge of the panel forms part of a trough.

(Original) 11. The container of claim 8, wherein a first diameter of the first ridge is less than, greater than or equal to a second diameter of the second ridge.

(Canceled) Claims 12-15.

(Previously Amended) 16. A container, comprising:

a finish;

a dome attached to the finish, the dome extend from the finish to a first ridge;

a body having a second ridge;

a reduced diameter portion connecting the first ridge and the second ridge;

a truss structure disposed in the reduced diameter portion, the truss structure being arranged continuously around at least a portion of a circumference of the container and being 20-40% thicker than the first and second ridges.

(Original) 17. The container of claim 16, wherein the truss comprises a plurality of panels, the panels having side edges adjacent to side edges of an adjacent panel and being alternately inclined and declined with respect to each other around the reduced diameter portion.

(Original) 18. The container of claim 16, wherein the truss structure includes a surface having a plurality of axial apexes and troughs alternately arranged around the circumference of the reduced diameter portion.

(Canceled) Claims 19-23.